

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
16 June 2005 (16.06.2005)


PCT

(10) International Publication Number
WO 2005/054030 A1

- (51) International Patent Classification⁷: **B61L 3/12**
- (21) International Application Number:
PCT/EP2004/053217
- (22) International Filing Date: 1 December 2004 (01.12.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
TO2003A 000978 5 December 2003 (05.12.2003) IT
- (71) Applicant (for all designated States except US):
ANSALDO SEGNALAMENTO FERROVIARIO S.p.A. [IT/IT]; Località Tito Scalo - Zona Industriale, I-85050 Tito (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **SABINA, Salvatore** [IT/IT]; Via Di Pratole, 75, I-56127 Pisa (IT). **SBRAGIA, Dante** [IT/IT]; Via Imperia, 2/49, I-16122 Genova (IT). **CANEPA, Giovanni** [IT/IT]; Via Alla Brigna, 14, I-16158 Genova (IT).
- (74) Agents: **JORIO, Paolo** et al.; Studio Torta S.r.l., Via Viotti, 9, I-10121 Torino (IT).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: RAILWAY BEACON AND RELATED PRODUCTION METHOD



(57) Abstract: A railway beacon having a casing (3) supporting an electronic circuit (4), which receives an electromagnetic enabling signal from a vehicle travelling along a railway line, and generates a coded response signal (telegram) transmitted to the vehicle. The casing (3) is formed in one piece from insulating material, and has at least one sunken seat (12a) housing the electronic circuit (4), which is embedded in a layer of insulating silicone resin (40) poured and set inside the sunken seat.

WO 2005/054030 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.